

Product Datasheet



SQ-80 Emergency Shower and Eyewash Station

Floor mounted Emergency shower and eyewash station
Fully stainless steel Combined with both Shower and eyewash function.

Specifications

TECHNICAL DATA	
INLET CONNECTION SIZE & TYPE	1 1/4" NPT (F thread)
DRAINAGE CONNECTION SIZE & TYPE	1 " NPT (Fthread)
SHOWER OPERATION	Pull Rod
EYE/FACE WASH OPERATION	Hand push
SUPPLY PRESSURE	2 bar minimum - 4.5bar maximum
FLOW AT OPERATING PRESSURE	Shower ≥ 76 litres/minute , Eye/Face wash ≥12 litres/minute
WORKING CONDITION	Water source temperature: 5-35℃, air temperature 5-37℃
OPTIONAL ACCESSORIES	Material update to SS316, surface coating, dimensions
MATERIALS OF CONSTRUCTION	
SHOWER HEAD	10 " Stainless Steel 304
VALVE MATERIALS	Stainless Steel 304
EYE/FACE WASH BOWL	10 " Stainless Steel 304
EYEWASH NOZZLE	Stainless steel 304
GROUND LEGS	Stainless Steel 304
PULL RODS FOR VALVE ACTIVATION	Stainless Steel 304
WEIGHTS AND DIMENSIONS	
ASSEMBLE DIMENSIONS (WxDxH)	74*26*23cm
WEIGHTS	12kg

GA Drawing

SQ-80

Emergency Shower and Eyewash Station

