

Product Datasheet

SQP-52 Portable Emergency Eyewash Station



Use good quality ABS plastic

Applied in area without fixed water source need. Small volume, easy to move and can be relocated

Specifications

TECHNICAL DATA	
EYE/FACE WASH OPERATION	Hand pull
INLET CONNECTION SIZE	68mm
FLOW AT OPERATING PRESSURE	Eye/Face wash - 1.2 litres/minute (0.3 US gallons)
WORKING CONDITION	Water source temperature: 5-35℃, air temperature 5-40℃
CAPACITY	30L
Remark:	Installation accessories like bracket and bolt is included
MATERIALS OF CONSTRUCTION	
BODAY	PE
LID	Rubber
WEIGHTS AND DIMENSIONS	
ASSEMBLE DIMENSIONS (WxDxH)	550mm (21.65in) x 250mm (9.84in) x 360mm (14.17in)
WEIGHTS	6kg (13.23lbs)

SQP-52

Portable Emergency Eyewash Station



No.	Description
1	Warning sign
2	Push plate lock
3	Handle
4	Inlet & Cover
5	Outlet tube
6	Eye wash nozzle
7	Push plate
Remark	
a.	Material: PE
b.	Gross weight: 6kgs
c.	Capacity: 30L
d.	Standard: ANSI Z358.1:2014
e.	Guarantee: 12 months